

PERSONNEL BUNKER PROTECTOR & END CAP



End Cap →

A molded, plastic system to mitigate blast and absorb fragmentation, shrapnel, and energy as a personnel protection enhancement. The molded, plastic, color-safe unit can be installed by hand and filled with sand to create 24 inches of minimum protection. Its ability to be quickly deployed and easily recoverable makes this an excellent system for your security needs.

The molded, plastic end treatment is designed to provide safety from blast and shrapnel. This unit is placed at the entrance of any opening, where blast mitigation or ballistic protection is needed. The end cap is designed to work with our Bunker Personnel Protector segments.

The fifteen (15) year UV unit is sand filled, eliminating the typical labor of intensive sand bagging. This unit is easily recovered and repositioned, as threat level or operation requirement dictates.

The front and rear treatment completes the ability to protect from small arms fire or ricochet.

SPECIFICATIONS:

END CAP -

SIZE:	EMPTY WT:	FILLED WT (SAND):	GSA NUMBER:
7 1/2' (H) x 36" (D) x 10' (W)	385 lbs	15,000 lbs	GS-07F-9503S
PERSONNEL PROTECTOR -			
7 1/5' (H) x 30" (D) x 10' (L)	385 lbs	9,450 lbs	GS-07F-9503S



223 North Main Street - Churubusco, IN 46723
 Phone: (800)- 860-2855 - (260) 432-7158
 Fax: (260) 459-0929 - Email: sales@soacorp.com
www.soacorp.com