



HIGH THREAT MANUAL STEEL SWING GATES

The High Threat Manual Swing Gates are either Engineer Rated or Certified to stop a 15,000 lbs. vehicle traveling at 30 MPH, 40 MPH or 50 MPH (K12). The standard gate is manually opened by raising bollard with attached wench, pulling gate pin and swinging the gate open.

* These gates have been (K12) certified by the Department of State (ASTM Standard 2656-07)



K12 CERTIFIED HEAVY DUTY STEEL SWING GATE - 6 FT. TALL

Part No.	Weight (lbs.)	Gate Width	Thru Diameter	Bollards
*32503	7,200	13'	11'	3
*32504	7,500	14'	12'	3
*32505	8,500	17'	15'	3
*32506	9,500	20'	18'	4

ENGINEERING RATED (50 MPH) HEAVY DUTY STEEL SWING GATE - 6 FT. TALL

Part No.	Weight (lbs.)	Gate Width	Thru Diameter	Bollards
32507	10,000	22'	20'	4
32508	12,000	26'	24'	5

ENGINEERING RATED (40 MPH) MEDIUM DUTY STEEL SWING GATE - 5 FT. TALL

Part No.	Weight (lbs.)	Gate Width	Thru Diameter	Bollards
22503	4,400	13'	11'	1
22504	4,500	14'	12'	1
22505	4,900	17'	15'	1
22506	5,200	20'	18'	1
22507	5,500	22'	20'	1
22508	6,000	26'	24'	1

PERIMETER SECURITY PRODUCTS

Email: sales@soacorp.com
 265 East Bell Drive, Warsaw, IN
 260-459-0456 (office)

www.perimetersecurityproducts.com



HIGH THREAT MANUAL STEEL SWING GATES

ENGINEERING RATED (30 MPH) REGULAR DUTY STEEL SWING GATE - 4 FT. TALL

Part No.	Weight (lbs.)	Gate Width	Thru Diameter	Bollards
12504	3,500	14'	12'	N/A
12505	3,600	17'	15'	N/A
12506	3,800	20'	18'	N/A
12507	3,900	22'	20'	N/A
12508	4,000	24'	22'	N/A



PERIMETER SECURITY PRODUCTS
Email: sales@soacorp.com
265 East Bell Drive, Warsaw, IN
260-459-0456 (office)
www.perimetersecurityproducts.com